

THE JENNISON-WRIGHT Co.

P.O. BOX 110591 CLEVELAND OHIO 44111-0591
(216) 671-5900 FAX (216) 671-1313
email: Sales@JennisonWright.com

KREOLITE[®] TOP-KOTE FILLER-SEALER No. J-1237[™]

DESCRIPTION:

KREOLITE Top-Kote Filler-Sealer No. J-1237 is an oil and acid resistant waterproof joint filler that is applied easily to both newly laid End Grain Wood Block and Heavy-Duty Rock Block Floor as well as to those floors that have been in use. Top-Kote Filler-Sealer No. J-1237 is a heavy bodied coal tar emulsion that does not have to be heated. It is applied cold and does not readily chip out between blocks when properly applied. It's excellent qualities aid in prolonging the life of wood block flooring and reduce maintenance costs.

APPLICATION:

Contents will settle in storage and transit. Thoroughly mix the coal tar as is packaged. Do not thin and do not heat. Apply Top-Kote Filler-Sealer No. J-1237 over new or properly prepared wood block floors with hard rubber hand squeegee and work into joints. Do not leave excess coating on top of floor block. Top-Kote Filler-Sealer No. J-1237 will be ready for heavy traffic in one day. If joints are not completely filled, another application may be required. Existing Block Floors should be scarified properly by mechanical means to insure proper adhesion. High humidity will retard the drying time.

COVERAGE:

Coverage will depend on depth of blocks and the width of joints.
New Block Floors: Estimate between 30 to 60 s/f per Gallon, two coats.
Existing Block Floors: Estimate between 30 to 120 s/f per Gallon, one coat.
New Floors or Existing Floors with deep joints will require 2 applications.
Packaged in 5 Pails.

CAUTION:

Contains Coal Tar. Avoid prolonged contact with skin and breathing of the vapor. If swallowed, do not induce vomiting. Contact Physician. Nonflammable. Keep from freezing. Consult Material Safety Data Sheet Prior To Use.

MISCELLANEOUS:

Also available are moisture and water resistant Heavy-Duty Rock Block, Polymer Jura Block, Steel Tile Anchor Floor Plates, Floor Block Trench Fillers, Adhesives and Special Coatings.

CAUTION: READ MATERIAL SAFETY DATA SHEET BEFORE USING ALL PRODUCTS. All statements and recommendations are based on experience we believe to be reliable. The use or application of these products being beyond the control of the seller or the manufacturer, neither the seller nor the manufacturer make any warranty expressed or implied, as to results or hazard from its use. The suitability, risk and liability of a product for any intended use shall be solely up to the user.