

THE JENNISON-WRIGHT CO.

P.O. BOX 110591 CLEVELAND OHIO 44111-0591
(216) 671-5900 FAX (216) 671-1313
email: Sales@JennisonWright.com

SUPER FLOOR BLOCK CEMENT No. J-1280™

DESCRIPTION:

Super Floor Block Cement No. J-1280 is specially formulated for the setting of any block flooring such as treated Wood Floor Block, Heavy Duty Rock Block, Fiber Block and Polymer Wood Jura-blocks™. Super Block Cement No. J-1280 is a black emulsion fortified with a latex resin to give it exceptional "Quick-Grab" strength. It is nonflammable and has no objectionable odor. Material has permanent flexibility, will not re-emulsify and because of its remarkable ability to stretch and recover, will not break loose.

APPLICATION:

No heating or mixing is required. Square-off area to be repaired. Clean base and apply material as it comes from the container using notched trowel to spread. Allow Super Floor Block Cement No. J-1280 to become tacky (about 15 minutes) before placing blocks into place. Blocks are then set in a staggered pattern firmly into place making sure rows are straight as possible. Wood Block floors must be sealed with Kreolite sealers according to Jennison-Wright Specifications to prevent excessive moisture absorption and seal against oil and water conditions.

COVERAGE

One gallon of Super Floor Block Cement No. J-1280 will adhere:
Wood blocks : 25-30 square feet.
All other blocks : 40-50 " "

CAUTION:

Keep from freezing. Rotate Stock. Packaged in 5 gallon containers. Consult Material Safety Data Sheet prior to use.

MISCELLANEOUS:

Also available are Moisture and water resistant Heavy Duty Rock Block, Polymer Wood Jura Blocks, Steel Tile Anchor Floor Plates, Floor Block Trench Fillers, Sealers and Special Coatings.

CAUTION: READ MATERIAL SAFETY DATA SHEET BEFORE USING ALL PRODUCTS. All statements and recommendations are based on experience we believe to be reliable. The use or application of these products being beyond the control of the seller or the manufacturer, neither the seller nor the manufacturer make any warranty expressed or implied, as to results or hazard from its use. The suitability, risk and liability of a product for any intended use shall be solely up to the user.