

THE JENNISON-WRIGHT Co.

P.O. BOX 110591 CLEVELAND OHIO 44111-0591

(216) 671-5900 FAX (216) 671-1313

email: Sales@JennisonWright.com

SEAL-(W)RIGHT®

BLACK

Product No. SW-103

Seal-(W)right SW103 is an EPA approved and cost effective jet black penetrating surface sealer designed for sealing creosoted treated wood block floors. (NOT A FILLER) Seal-(W)right SW-103 will offer superior adhesion to a creosoted treated wood block floor that is clean and has not been scarified by mechanical means. Water based sealers tend to "lay on the surface" and may peel on a floor that has not been properly prepared and will not seal creosote treated wood properly.

Seal-(W)right SW-103 prevents bleeding of the creosote and tracking of hot pitch and cold fillers onto adjoining areas such as into offices, corridors and other decorative floor surfaces. Sealed surfaces minimize oil and water absorption, reduce floor maintenance, improve the appearance and make old looking floors like new again.

INSTRUCTIONS:

Floors should be reasonably cleaned and free of excess oil, grease, dirt, etc. Allow floor to dry thoroughly before applying the sealer. Newly laid floors that have been set with hot pitch may be sealed almost immediately. Floors set with cold adhesives and coal tar fillers require additional setting time before finally sealing. No heating or mixing is required and application may be with a lamb's wool applicator, brush, or flexible squeegee. Use alcohol to clean equipment.

COVERAGE:

50 to 300 square feet per gallon. Two coats are recommended.

DRYING TIME:

Dust free in 60 minutes. May be opened up to foot traffic within three to four hours depending upon temperature and humidity. Allow 12-24 hours for heavier traffic.

CAUTION:

Flammable liquid, contains isopropyl alcohol. Consult material safety data sheet and product label before using. Seal-(W)right SW-103 is not intended to be used as an, adhesive or filler. Observe safety and fire precautions during handling, storage, application and curing. Keep all containers closed when not in use and store in a cool dry place. Avoid applying the sealer near heat or flame during production or maintenance shutdowns and have workmen wear appropriate chemical respirator when working.

REMARKS:

Seal-(W)right SW-103 is non-tacky for storage areas and colored aisle marking paints may be applied without any special preparation. Packaged in 5 and 55 gallon containers.

MISCELLANEOUS:

Also available are End Grain Wood Floor Blocks, Heavy-Duty Rock Block, Polymer Jura Block, Steel Tile Anchor Floor Plates, Floor Block Trench Fillers, Adhesives and Special Coatings.

CAUTION: READ MATERIAL SAFETY DATA SHEET BEFORE USING ALL PRODUCTS. All statements and recommendations are based on experience we believe to be reliable. The use or application of these products being beyond the control of the seller or the manufacturer, neither the seller nor the manufacturer make any warranty expressed or implied, as to results or hazard from its use. The suitability, risk and liability of a product for any intended use shall be solely up to the user.